



# MM17

Patient Monitor



# MM17

## Patient Monitor



### Configurable Interfaces:



Large Font



OxyCRG



Standard



Trend Screen

### Features:

- The plug-and-play modular design of the MM17 brings flexibilities to critical cares. Meantime, it offers an easy click-and-switch function to switch between modules with its intuitive MeasureSet Management interface.
- XM1 Module
- Standard: 3/5-lead ECG, NIBP, SpO2, PR, RR, TEMP
- Optional: 12-lead ECG, 2-IBP
- V-SpO2 Module ( Nellcor OxiMax SpO2)
- V-NIBP Module (OMRON NIBP)
- V-IBP Module (Maximum 8-IBP)
- V-C.O. Module (Thermal Dilution Cardiac Output)
- V-CO2 Module (Respironics Mainstream/Sidestream)
- V-AG Module (PHASEIN Mainstream/Sidestream/O2)

### Power-off Storage:

- USB Flash Disk
- SD Card

### External Communications:

- Ethernet
- Bed-to-bed View
- Nurse Call
- VGA/DVI Video Output

### Night Mode:

- Night mode with dimmer screen, backlit buttons, lower alarm volume and no HR beeps.

## Technical Specifications

### Physical Specification

Size: 425 mm (L) × 245 mm (W) × 382 mm (H)  
 Weight: Standard Configuration 14.5 kg  
 Display: 17" Full Touch-screen Color TFT

Resolution: 1280×1024 dpi  
 Traces Displayed: up to 8  
 Waveforms Displayed: up to 13  
 Various Working Interface Selectable:

Standard Monitoring Display  
 Large Font Intensive Care Display  
 Trend Graph/ Monitoring Co-Display  
 Bed to Bed view Display (Optional)  
 OxyCRG Dynamic View Display  
 Drug Dose Calculation Interface  
 6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s

### Sweep Speed:

### Environment Requirement

Ambient Temperature: -20°C - 55°C (-4 - 131°F)  
 Humidity: 15%-95% non-condensing

### Power Supply

External Power Supply: 100-240V AC, 50/60HZ  
 Internal Battery Power Supply: Rechargeable Li-ion 4200 mAh 14.8 V DC 2100 mAh (optional)

### RESP

Method: Trans-thoracic impedance  
 Operation mode: Auto/ Manual  
 RR Measurement range: Adult: 0~120 rPM  
 Neonate/Pediatric: 0~150 rPM  
 1rPM

Resolution: 10s, 15s, 20s (default), 25s, 30s, 35s, 40s  
 Alarm: 3 levels of audible and visual alarm, alarm events recallable

Band width: 0.2-2.5Hz (-3dB)  
 Sweep speed: 6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s

### ECG

Lead type: 5-lead and 3-lead selectable, 12-lead optional  
 3 leadwire cable: RA; LA; LL or R; L; F  
 5 leadwire cable: RA; LA; RL; LL; V or R; L; N; F; C (including 3/5-lead) optional  
 12-lead: 10 leadwire cable: RA; LA; RL; LL; V1-V6 or R; L; N; F; C1-C6

Lead selection: 3-lead: I; II; III;  
 5-lead: I; II; III; aVR; aVL; aVF; V  
 12-lead: I; II; III; aVR; aVL; aVF; V1-V6  
 Gain selection: x0.125; x0.25; x0.5; x1; x2; x4; auto  
 Sweep speed: 6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s  
 ECG HR Range: Adult: 15-300bpm  
 Pediatric / Neonate: 15-350bpm

Resolution & accuracy: ±1bpm or ±1%, whichever is greater  
 Filter Diagnostic mode: 0.05-100Hz or 0.05-150Hz (optional 12-lead)  
 Filter Monitoring mode: 0.5-40 Hz  
 Surgical mode: 1-20Hz  
 Protection: Withstand 5000VAC/50Hz voltage in isolation against Defibrillation and electrosurgical interference

ST-Segment Detection: Measurement range: -2.0 mV~2.0mV  
 Alarm range: -2.0 mV~2.0mV

ST-Segment Arrhythmia analysis and categorization: Yes  
 Alarm: 3 levels of audible and visual alarm, alarm events recallable

12 lead ECG analysis: 208 Reference Diagnostic Results  
 Pace maker detection: Yes, and 5 types abnormal status detectable Arrhythmia verification compliant with AHA and MIT-BIH databases

IEC 60601-2-25 / EN 60601-2-25 / AAMI EC 11 / EC 13  
 IEC 60601-2-27 / EN 60601-2-27

NIBP  
 Method: Automatic Oscillometric  
 Operation modes: Manual/Automatic/Continuous  
 Auto measurement time interval: Adjustable 1/2/3/4/5/10/15/30/60/90/120/240/480 Minutes

Measurement unit: mmHg/kPa selectable  
 Measurement types: Systolic, Diastolic, Mean  
 Pressure range for Adults: Systolic: 40 - 270 mmHg  
 Diastolic: 10 - 215 mmHg  
 Mean: 20 - 235 mmHg

Pressure range for Pediatrics: Systolic: 40 - 200 mmHg  
 Diastolic: 10 - 150 mmHg  
 Mean: 20 - 165 mmHg  
 Pressure range for Neonates: Systolic: 40 - 135 mmHg  
 Diastolic: 10 - 100 mmHg  
 Mean: 20 - 110 mmHg

Leak test and pressure auto calibration: Yes  
 Over-pressure protection: Dual Safety protection  
 Resolution: 1mmHg  
 Accuracy: Max mean error ±5mmHg  
 Max standard deviation: ±8 mmHg  
 Alarm: Systolic, Diastolic, Mean  
 PR from NIBP: Measurement 40~240 bpm  
 Resolution: 1 bpm  
 Accuracy: 3bpm or 3% whichever is greater

Leak test and pressure auto calibration: Yes  
 IEC 60601-2-30 / EN 60601-2-30 / EN 1060-1 / EN 1060-3 / EN 1060-4 SP10:2002

NIBP (By Omron M3600)  
 Measurement Ranges  
 Adult/Pediatric: Pulse Rate: 40 - 200bpm  
 Systolic Pressure: 60 - 250mmHg  
 Diastolic Pressure: 40 - 200mmHg  
 Mean Arterial Pressure: 45 - 235mmHg

Neonate: Pulse Rate: 40 - 240bpm  
 Systolic Pressure: 40 - 120mmHg  
 Diastolic Pressure: 20 - 90mmHg  
 Mean Arterial Pressure: 30 - 100mmHg  
 Measurement Accuracy: Pulse Rate: ±2bpm or 2% of reading whichever is greater  
 Blood Pressure: Complies with ANSI/AAMI SP10:2002

Modes of Measurement: Manual, Long-term automatic, Short-term automatic, Smart Inflation, Smart measurement, High speed  
 Pressure Transducers: Two independent solid-state  
 Deflation Methods: Dynamic Linear Deflation rate specific to pulse rate

## Technical Specifications

(Cont.)

### SpO2

Measurement & Alarm Range: 0 - 100%  
Resolution: 1%;  
Accuracy:  $\pm 2\%$  (70-100%, Adult/Pediatric);  
 $\pm 3\%$  (70-100%, Neonate)

PR Measurement and Alarm Range: 30 - 300bpm  
Resolution: 1bpm  
Accuracy: 3bpm Refresh 1s  
ISO 9919

### SpO2 (By Nellcor OxiMax™)

Measurement & Alarm Range: 0 - 100%  
Resolution: 1%;  
Accuracy:  $\pm 2-3\%$  (70-100%, Adult/Pediatric);  
 $\pm 3-3.5\%$  (70-100%, Neonate)

PR Measurement and Alarm Range: 20 - 300bpm  
Resolution: 1bpm  
Accuracy: 3bpm (depends on probe)

### Temperature (2 Channels, 1 probe by default)

Measurement range: 0~50°C (32-122°F)  
Resolution: 0.1°C  
Accuracy:  $\pm 0.1^\circ\text{C}$  (without probe)  
Channel: Dual-channel. Provide T1; T2; T Δ  
IEC 12470-4

### IBP (Multi-channel extendable)

Measured Pressure: ART, PA, CVP, RAP, LAP, ICP, P1,P2  
Measurement range: -50 - 300 mmHg;  
Resolution: 1 mmHg  
Accuracy:  $\pm 2\%$  or  $\pm 1\text{mmHg}$ , whichever is greater  
(without probe)  
Sensitivity:  $5\mu\text{V/V/mmHg}$ ;  
Impedance range: 300-3000  $\Omega$   
IEC 60601-2-34

### CO2 (Mainstream / Sidestream)

By Philips Respronics CAPNOSTAT 5 & LoFlo Technology  
Range: 0~ 150mmHg  
Accuracy:  $\pm 2\%$  0 ~ 40mmHg,  
 $\pm 5\%$  41~70mmHg  
 $\pm 8\%$  71~100mmHg  
 $\pm 10\%$  101~150 mmHg  
AwRR Accuracy:  $\pm 1\text{rpm}$

Convenient design for intubated and non-intubated applications  
Possible to work at low sample flow rate: 50ml / minute  
Detailed specification refer to the user manual of Respronics  
ISO 21647

### Cardiac Output

Method: Thermodilution Technology  
Measuring range: CO: 0.1 ~ 20L/min  
TB: 23°C ~ 43°C  
TI: - 1°C ~ 27°C  
Alarm range 23°C ~ 43°C

### Anesthetic GAS/O2

Technology Infra-red absorption characteristic  
Paramagnetic Oxygen: Optional  
Gas: CO2, O2, N2O, Des, Iso, Enf, Hal, Sev  
(IRMA AX+) Iso accuracy mode: 45s  
Warm-up time: (IRMA AX+) Iso accuracy mode: 45s  
Full accuracy mode: 60s  
(ISA OR+ / AX+) <20s  
Sample flow rate (for ISA OR+ / AX+) 50  $\pm$  10 ml/min  
Measuring range: CO2: 0 ~ 15%  
N2O: 0 ~ 100%  
Hal/Iso/Enf: 0 ~ 8% Sev: 0~10%  
Des: 0 ~ 22%  
O2: 0 ~ 100%(ISA OR+/AX+)  
Respiratory Rate: 0-150bpm  $\pm$  1bpm

MAC Value displayed  
ISO 21647

### Thermal Recorder

Built-in, direct thermal pixel array recorder  
2 channels printing and 1,2 channels selectable  
Up to 3 channels printing and 1,2,3 channels selectable (to be released)  
Print speed: 25mm/s, 50mm/s (to be released)  
Paper width: 50 mm

### I/O Interface

8-USB Ports  
SD Card Socket  
RS-232 Serial Port  
RJ-45 Ethernet Port. IEEE 802.3 DVI output  
VGA output  
Analog and Nurse Call output Defibrillation Synchronization Output  
WLAN Access Point 802.11g 54Mbps (optional)

### Optional Modules:



MM<sup>3</sup> Module



MM + Module



Parameter Amplifier  
Mainframe

# Mediblu